



ControlMatrix® II Series

CM2-10d™ Wall-mount and Desktop Paging Stations

The CM2-10d is a rugged and capable digital paging station designed for direct connection to Cobranet networks. The CM2-10d features the latest PoE (Power over Ethernet) technology and/or local or remote DC low voltage power. All connections to the CM2-10d are accomplished through a single Ethernet network cable termination via a standard 8P8C modular connector (commonly called an RJ-45) for easy installation and service. A high quality microphone preamplifier and analog to digital converter is included providing the required digital audio to the network interface.

The CM2-10d Wall-mount Paging Station includes a handheld dynamic microphone with a PTT (Push-To-Talk) switch, while the CM2-10d Desktop Paging Station includes a gooseneck condenser microphone.

- Easily configurable for administrative or user paging with ControlMatrix II software.
- Operates on PoE (Power over Ethernet) or low voltage DC power.
- Uses standard Ethernet network connectivity.
- High impact ABS plastic enclosure with nonslip rubber feet for desktops or flush mounted with a steel backing box.
- Back-lit 2 line by 20 character front panel LCD display.
- Handheld dynamic microphone or gooseneck condenser microphone.
- Integrated microphone pre-amplifier and analog to digital convertor.
- Additional RJ-45 jack for connecting a remote microphone panel.

ControlMatrix® II Series

CM2-10d™ Paging Station

FRONT PANEL FEATURES:

- Back-lit 2x20 LCD Display
- Ten additional zone selection buttons
- 5-pin XLR for handheld dynamic microphone with PTT (wall-mount) or 3-pin XLR for gooseneck microphone (desktop) with gain adjustment
- 12-key touch pad
- PTT microphone clip (wall-mount only)

AUDIO INPUTS:

- Front panel 5-pin XLR for handheld dynamic microphone (wall-mount)
- Front panel 3-pin XLR for gooseneck condenser microphone (desktop)
- RJ45 connection for extending microphone service to an RMP-2 remote microphone panel

MICROPHONE:

- Noise cancelling dynamic communications microphone with TALK switch, black neoprene coiled cable harness terminated with male 5-pin XLR (wall-mount)
- Gooseneck condenser microphone with cardioid pickup pattern

DATA INTERFACE:

- Ethernet 8P8C modular plug jack (RJ-45 jack) for connection to a standard Ethernet network Power:
- PoE-Power over Ethernet - for use with PoE equipped network switch hardware

MOUNTING:

- ABS enclosure with non-slip rubber feet for desktop applications
- Galvanized steel backing box for wall-mount applications



Logo referenced in Directive 2002/96/EC Annex IV (OJ(L)37/38, 13.02.03 and defined in EN 50419: 2005
The bar is the symbol for marking of new waste and is applied only to equipment manufactured after 13 August 2005



Commercial Audio

Features and specifications subject to change without notice.

Peavey Electronics Corporation
5022 Hartley Peavey Drive
Meridian, MS 39305
(601) 483-5365 • FAX (601) 486-1278 • www.peavey.com

PRINTED IN THE U.S.A.

06/2013