

Kiosk™ 180^{HD}

Touch-Screen Controller

MediaMatrix®



Description

The new MediaMatrix Kiosk™ 180^{HD} features a clean modern design that can be mounted in any number of handy locations to provide a rich graphical user interface that can be tailored to any control requirement. New high resolution graphics and a responsive capacitive touch screen provide the user experience that your customers now expect.

Features

- Sharp 16:9 ratio 7" diagonal high resolution display
- Responsive capacitive touch interface
- Flexible mounting options
- Silent convection cooled operation
- Universal external agency approved power supply
- Improved processor power and speed
- Robust industrial operating system

Features and specifications subject to change without notice.

Peavey Electronics Corporation • 5022 Hartley Peavey Drive • Meridian, MS 39305
Phone: (601) 483-5365 • Fax: (601) 486-1678 • www.peaveycommercialaudio.com



Commercial Audio

Kiosk™ 180^{HD} - Touch Screen Controller

Specifications

| Kiosk 180 ^{HD} | | |
|-------------------------|----------------------------------------------------|------------------------------------------------|
| LCD | Size | 7" |
| | Resolution | 1024 x 600 (16:9) |
| | Brightness (cd/m ²) | 500 |
| | Contrast Ratio | 700:1 |
| | LCD Color | 16.2M |
| | Pixel Pitch (mm) | 0.0635 (H) x 0.1905 (V) |
| | Viewing Angle (H-V) | 150° / 145° |
| | Backlight MTBF (hrs) | 2000 hrs |
| Touch | Touch Screen | Projected Capacitive Type |
| | Touch Controller | EETI EXC3160 |
| Motherboard | CPU | Dual Core Intel Celeron N2807 |
| | RAM | 2GB DDR3L |
| | Ethernet | 2 x PCIe GbE by RTL8111E Controller |
| Storage | | mSATA |
| I/O Ports & Switch | 2 x RS-232 COM port (DB-9 connector) | |
| | 2 x USB 3.0 | |
| | 2 x GbE LAN | |
| | 1 x Power Switch | |
| | 1 x Reset Button | |
| | 1 x AT/ATX Switch | |
| | 1 x 9-30V Lockable Power Jack | |
| Audio | | AMP 2W (internal speaker, left channel output) |
| OSD Function | | Software OSD |
| Physical | Front Panel Constuction | PC + ABS Plastic |
| | Mounting | Panel, Wall, Stand, Arm / VESA 75mm x 75mm |
| | Color | Black C |
| | Dimensions (WxHxD) (mm) | 191 x 127 x 43 |
| | Cut-out Dimensions (WxH) (mm) | 182 x 111 |
| | Net Gross Weight (kgs) | 0.73 / 1.81 |
| Environment | Operating Temperature (C°) (Ambient with air flow) | -20°C~50°C |
| | Storage Tempature (C°) | -20°C~60°C |
| | Humidity | 10% to 95% (non-condensing) |
| | IP Level | IP 65 compliant front panel |
| | Safety & EMC | CE / FCC |
| | Thermal Solution | Fanless |
| Power | Power Requirement | 9 V ~ 30 V |
| | Power Consumption | 12V@2.08 |