



CPL™ + Series

Hybrid Loudspeakers

A new standard for fixed installation and live applications.



CPL™+ Series

The Perfect Match for Every Venue

The Crest Audio CPL+ Series offers twelve versatile loudspeaker system configurations, with various mounting options to accommodate a wide range of install and live applications. This hybrid design makes them the perfect choice for classrooms, meeting facilities, restaurants, clubs, bars, and live venues. They are also ideal for environments where spoken-word intelligibility is critical, such as courtrooms, house of worship, auditoriums, sport venues, and transportation facilities.

CPL+ SERIES FEATURES

- 12 complementary speaker models
- Neodymium high-frequency components*
- 4-pin Euroblock and 2x4-pin twist-lock connectors
- Multiple mounting & flying options
- All models available in black or white
- 2+/- Loop through connectivity
- Sturdy plywood construction
- Advanced crossover network*
- EASE GLL files for all models



**On select models*



CPL 5C+

Item # 04002450

System Configuration:
 Power Rating:
 Sensitivity (1W/1m) / max. SPL Peak:
 Frequency Range (-10 dB):
 Frequency Response (± 3 dB):
 Nominal Impedance:
 LF Driver:
 HF Driver:
 Nominal Coverage (HxV):
 Suspension Points:
 Weight:
 Dimensions (HWD):

2-way Ultra-compact Coaxial Passive Loudspeaker
 100W Continuous / 400W Peak
 92 dB / 118 dB
 91 Hz - 20 kHz
 261 Hz - 20 kHz
 16 Ohms
 1 x 5" (130 mm), VC 1.5" (38 mm)
 1 x 1" Neo (25.4 mm), VC 1.4" (36 mm)
 80° x 80°
 3 x M8 (U-Bracket included)
 11.6 lbs (5.3 kg)
 7.28" x 7.28" x 8" (185 x 185 x 203 mm)



Item # 04002450

CPL 25C+

Item # 04002460

System Configuration:
 Power Rating:
 Sensitivity (1W/1m) / max. SPL Peak:
 Frequency Range (-10 dB):
 Frequency Response (± 3 dB):
 Nominal Impedance:
 LF Driver:
 HF Driver:
 Nominal Coverage (HxV):
 Suspension Points:
 Weight:
 Dimensions (HWD):

2-way Ultra-compact Coaxial Passive Loudspeaker
 200W Continuous / 800W Peak
 94 dB / 123 dB
 91 Hz - 20 kHz
 132 Hz - 20 kHz
 8 Ohms
 2 x 5" (130 mm), VC 1.5" (38 mm)
 1 x 1" Neo (25.4 mm), VC 1.4" (36 mm)
 80° x 80°
 3 x M8 & 4 x M6 (U-Bracket included)
 20 lbs (9.1 kg)
 14.96" x 7.01" x 7.4" (380 x 178 x 188 mm)



Item # 04002730

CPL 6+

Item # 04002370

System Configuration:
 Power Rating:
 Sensitivity (1W/1m) / max. SPL Peak:
 Frequency Range (-10 dB):
 Frequency Response (± 3 dB):
 Nominal Impedance:
 LF Driver:
 HF Driver:
 Nominal Coverage (HxV):
 Suspension Points:
 Weight:
 Dimensions (HWD):

2-way Ultra-compact Passive Loudspeaker
 75W Continuous / 300W Peak
 92 dB / 117 dB
 73 Hz - 19 kHz
 130 Hz - 17 kHz
 16 Ohms
 1 x 6.5" (165 mm), VC 1.2" (30 mm)
 1 x 1" (25.4 mm), VC 1" (25.4 mm)
 90° x 60°
 9 x M8 & 4 x M6
 14.3 lbs (6.5 kg)
 12.52" x 8.78" x 8.98" (318 x 223 x 228 mm)



Item # 04002640

CPL 26+

Item # 04002420

System Configuration:
 Power Rating:
 Sensitivity (1W/1m) / max. SPL Peak:
 Frequency Range (-10 dB):
 Frequency Response (± 3 dB):
 Nominal Impedance:
 LF Driver:
 HF Driver:
 Nominal Coverage (HxV):
 Suspension Points:
 Weight:
 Dimensions (HWD):

2-way Compact Passive Loudspeaker
 150W Continuous / 600W Peak
 95 dB / 122 dB
 77 Hz - 20 kHz
 153 Hz - 18.3 kHz
 8 Ohms
 2 x 6.5" (165 mm), VC 1.2" (30 mm)
 1 x 1" (25.4 mm), VC 1.3" (34 mm)
 90° x 40°
 9 x M8 & 4 x M6
 24.9 lbs (11.3 kg)
 23.25" x 8.81" x 9.5" (591 x 224 x 241 mm)



Item # 04002690

CPL 8+

Item # 04002380

System Configuration: 2-way Compact Passive Loudspeaker
 Power Rating: 200W Continuous / 800W Peak
 Sensitivity (1W/1m) / max. SPL Peak: 95 dB / 124 dB
 Frequency Range (-10 dB): 67 Hz - 20 kHz
 Frequency Response (± 3 dB): 131 Hz - 20 kHz
 Nominal Impedance: 8 Ohms
 LF Driver: 1 x 8" (200 mm), VC 2" (50 mm)
 HF Driver: 1 x 1" (25.4 mm), VC 1.3" (34 mm)
 Nominal Coverage (HxV): 60° x 60°
 Suspension Points: 9 x M8 & 4 x M6
 Weight: 24.6 lbs (11.2 kg)
 Dimensions (HWD): 16.54" x 10.59" x 10.83" (420 x 269 x 275 mm)



Item # 04002650

CPL 10+

Item # 04002390

System Configuration: 2-way Compact Passive Loudspeaker
 Power Rating: 300W Continuous / 1,200W Peak
 Sensitivity (1W/1m) / max. SPL Peak: 96 dB / 126 dB
 Frequency Range (-10 dB): 51 Hz - 20 kHz
 Frequency Response (± 3 dB): 88 Hz - 20 kHz
 Nominal Impedance: 8 Ohms
 LF Driver: 1 x 10" (250 mm), VC 2.5" (65 mm)
 HF Driver: 1 x 1" (25.4 mm), VC 1.4" (36 mm)
 Nominal Coverage (HxV): 90° x 60° (Rotatable)
 Suspension Points: 12 x M8 & 4 x M6
 Weight: 33 lbs (15 kg)
 Dimensions (HWD): 20.87" x 12.56" x 13.39" (530 x 319 x 340 mm)



Item # 04002660

CPL 12+

Item # 04002400

System Configuration: 2-way Passive Loudspeaker
 Power Rating: 350W Continuous / 1,400W Peak
 Sensitivity (1W/1m) / max. SPL Peak: 96 dB / 127 dB
 Frequency Range (-10 dB): 49 Hz - 20 kHz
 Frequency Response (± 3 dB): 75 Hz - 20 kHz
 Nominal Impedance: 8 Ohms
 LF Driver: 1 x 12" (305 mm), VC 3" (76 mm)
 HF Driver: 1 x 1" (25.4 mm), VC 1.4" (36 mm)
 Nominal Coverage (HxV): 90° x 60° (Rotatable)
 Suspension Points: 16 x M8
 Weight: 45.5 lbs (20.7 kg)
 Dimensions (HWD): 23.82" x 14.49" x 15.35" (605 x 368 x 390 mm)



Item # 04002670

CPL 15+

Item # 04002410

System Configuration: 2-way Passive Loudspeaker
 Power Rating: 500W Continuous / 2,000W Peak
 Sensitivity (1W/1m) / max. SPL Peak: 97 dB / 131 dB
 Frequency Range (-10 dB): 47 Hz - 20 kHz
 Frequency Response (± 3 dB): 66 Hz - 17.8 kHz
 Nominal Impedance: 8 Ohms
 LF Driver: 1 x 15" (381 mm), VC 3" (76 mm)
 HF Driver: 1 x 1" (25.4 mm), VC 1.4" (36 mm)
 Nominal Coverage (HxV): 90° x 60° (Rotatable)
 Suspension Points: 16 x M8
 Weight: 67.2 lbs (30.5 kg)
 Dimensions (HWD): 27.36" x 17.36" x 17.52" (695 x 441 x 445 mm)



Item # 04002680

CPL 4L+



Item # 04002490

System Configuration:
Power Rating:
Sensitivity (1W/1m) / max. SPL Peak:
Frequency Range (-10 dB):
Frequency Response (± 3 dB):
Nominal Impedance:
LF Driver:
Nominal Coverage (HxV):
Suspension Points:
Weight:
Dimensions (HWD):

Passive Column Array Speaker
120W Continuous / 480W Peak
93 dB / 120 dB
150 Hz - 20 kHz
206 Hz - 13 kHz
8 Ohms
4 x 3" (76 mm), VC 0.75" (20 mm)
90° x 25°
7 x M8
6 lbs (2.7 kg)
17.52" x 4.72" x 4.98" (445 x 121 x 126.5 mm)



Item # 04002760

CPL 8L+



Item # 04002500

System Configuration:
Power Rating:
Sensitivity (1W/1m) / max. SPL Peak:
Frequency Range (-10 dB):
Frequency Response (± 3 dB):
Nominal Impedance:
LF Driver:
Nominal Coverage (HxV):
Suspension Points:
Weight:
Dimensions (HWD):

Passive Column Array Speaker
240W Continuous / 960W Peak
96 dB / 126 dB
130 Hz - 20 kHz
175 Hz - 13.9 kHz
4 Ohms
8 x 3" (76 mm), VC 0.75" (20 mm)
90° x 20°
7 x M8
10.7 lbs (4.9 kg)
33.74" x 4.72" x 4.98" (857 x 121 x 126.5 mm)



Item # 04002770

CPL 265B+



Item # 04002440

System Configuration:
Power Rating:
Sensitivity (1W/1m) / max. SPL Peak:
Frequency Range (-10 dB):
Frequency Response (± 3 dB):
Nominal Impedance:
LF Driver:
Suspension Points:
Weight:
Dimensions (HWD):

Ultra-compact Passive Subwoofer
100W Continuous / 400W Peak
94 dB / 120 dB
53 Hz - 200 Hz
65 Hz - 173 Hz
4 Ohms
2 x 6.5" (165 mm), VC 1.2" (30 mm)
3 x M8 & 1 x M20 pole-mount (U-Bracket included)
25.3 lbs (11.5 kg)
9.45" x 18.5" x 14.57" (240 x 470 x 370 mm)



Item # 04002710

CPL 15B+



Item # 04002430

System Configuration:
Power Rating:
Sensitivity (1W/1m) / max. SPL Peak:
Frequency Range (-10 dB):
Frequency Response (± 3 dB):
Nominal Impedance:
LF Driver:
Suspension Points:
Weight:
Dimensions (HWD):

Passive Subwoofer
500W Continuous / 2,000W Peak
95 dB / 128 dB
37 Hz - 2 kHz
49 Hz - 2 kHz
8 Ohms
1 x 15" (381 mm), VC 4" (100 mm)
1 x M20 pole-mount
78.2 lbs (35.9 kg)
27.38" x 18.56" x 20.08" (695 x 471 x 510 mm)



Item # 04002700



CPL 8+ with Pole Mount Adapter Small
CPL-PM-S-BK



CPL 8+ with U-Bracket
CPL-UB-8



CPL 8+ with Versamount™
VM 35



CPL 4L+ with Column Pole Mount Adapter
CPL-PM-C-BK




CPL 4L+ with Column Wall Mount Adapter
CPL-WM-C

The CPL+ Series features unobtrusive, flyable enclosures that are designed to be both attractive and discreet. A wide variety of mounting and flying options are available, including multiple eyebolt flying points, U-brackets, Versamount, special wall mount, and pole mount adapters. These options make the CPL+ Series incredibly easy to install and use in any setting.

Type	Model	CPL 5C ⁺	CPL 25C ⁺	CPL 6 ⁺	CPL 26 ⁺	CPL 8 ⁺	CPL 10 ⁺	CPL 12 ⁺	CPL 15 ⁺	CPL 4L ⁺	CPL 8L ⁺	CPL 265B ⁺	CPL 15B ⁺	Item # Black	Item # White
U-BRACKETS	CPL-UB-5C	✓												04002600	04002850
	CPL-UB-25C		✓											04002610	04002860
	CPL-UB-6			✓										04002530	04002790
	CPL-UB-26				✓									04002580	04002840
	CPL-UB-8					✓								04002540	04002800
	CPL-UB-10						✓							04002550	04002810
	CPL-UB-12							✓						04002560	04002820
	CPL-UB-15								✓					04002570	04002830
	CPL-UB-265B											✓		04002620	04002870
Wall Mounts	CPL-WM-C									✓	✓			04002520	04002780
	Versamount 35		✓	✓	✓	✓	✓							03010770	03010760
	Versamount 70		✓	✓	✓	✓	✓	✓	✓					03011050	03011040
Pole Mounts	CPL-PM-C-BK									✓	✓			04002510	n/a
	CPL-PM-S-BK		✓	✓	✓	✓	✓							04002590	n/a
	CPL-PM-L-BK							✓	✓					04002630	n/a
Various	M20 Poles											✓	✓	n/a	n/a
	Eyebolts	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓		n/a	n/a
		✓	included				✓	optional (available from Crest Audio)		✓	optional (not available from Crest Audio)				



Lila Brown - Indonesia
Using CPL 25C+ and CPL 265B+



Features and specifications subject to change without notice.

Peavey Electronics Corporation • 5022 Hartley Peavey Drive • Meridian, MS 39305
Phone: (601) 483-5365 • Fax: (601) 486-1278 • www.peaveycommercialaudio.com



Commercial Audio